SITE PLAN PACKAGE



CITY OF FAIRFAX

Department of Community Development and Planning Zoning Division 10455 Armstrong Street, Room 207A Fairfax, VA 22030 Phone: 703-385-7820 / Fax: 703-385-7824

February 2015

TO THE APPLICANT:

Except for individual single-family home construction, a site plan is required for all site construction, including new buildings, additions, remodeling, and site renovations. The entire process, from initial submission to final approval (including bond approval) takes approximately six months. Some applications will be processed in a shorter time period, some longer, depending on the complexity of the project.

The site plan review process is initiated by the applicant's pre-submission meeting with staff, followed by submission of a complete site plan and review fee. The submitted site plan is reviewed for Code compliance and then returned to the applicant for corrections. After review of the site plan, the applicant will be advised of any additional approvals that may be needed to support the project (Special Exceptions, Variances, Special Use Permits, or Subdivision actions). All architectural and landscape features, and in certain instances signage, must be approved by the Board of Architectural Review, prior to completing the plan review process. Subsequent to first submission, the applicant shall work directly with Fairfax Water to obtain their approval.

When all additionally required approvals have been obtained, the site plan can be submitted for final review. Bond and site agreements, clearing and grading permit applications, erosion and siltation agreements, and all other improvement bonds, agreements, and fees must be submitted with the final plan. The site plan will be approved by the Public Works Director and released to the applicant when it is technically correct and all bonding and fee requirements are met. Building permits can be released once bonding is complete.

Upon satisfactory completion of construction, a Residential Use Permit or Non-Residential Use Permit may be obtained. Bonds will be released after an as-built plan and a warranty bond are submitted, reviewed, and approved. The warranty bond will be released after passing final site inspection pending completion of the bond release process including the final site inspection of all warranty improvements.

The attached explanatory materials regarding the site plan review process will assist in preparation of your plan. If you have questions pertaining to the process, please contact the Zoning Division of the Department of Community Development and Planning at 703.385.7820.

Very truly yours,

Nancy Cranmer Deputy Zoning Administrator - Plans

CONTENTS

Guide to Site Plan review process	Page 4
Site Plan Application Form	Page 9
Agent Authorization Form	Page 11
Site Plan Signature Block	Page 14
Site Plan Checklist	Page 16
Site Plan Notes	Page 28
Fee Calculation sheet	Page 36
VSMP Fee Sheet & Checklist	
see http://fairfaxva.gov/government/public-works/sto	ormwater-and-
floodplain-management/virginia-stormwater-manage	ement-program-vsmp-
Site Plan Notification (sample)	Page 39
Water Quality Impact Assessment & Waiver Application	Page 41
Tree Removal Permit Application	Page 47
Grading Permit Application	Page 50
Site Plan Ordinance	
Digital Data Submission Requirements for GIS	Page 65
As-Built Review Checklist	Page 67
Surety Value Estimate	
see http://fairfaxva.gov/home/showdocument?id=435	<u>53</u>

IMPORTANT PHONE NUMBERS All AREA CODE (703)

289-6363
385-7810
385-7830
246-2541
385-7930
385-7810
385-7820
385-7893
385-7820
385-7930

PLEASE NOTE: Failure to obtain City approval for changes to an approved Site Plan or to install improvements and facilities according to the City approved plan **could result in civil penalty fines and other legal remedies** available to the City.

CITY OF FAIRFAX APPLICANT'S GUIDE FOR SITE PLAN REVIEW AND BOND RELEASE PROCESS

Submit all Site Plans, applications and bonding documents to:

City of Fairfax

City Hall Annex, Room 207

Department of Community Development and Planning

Zoning Division

10455 Armstrong Street

Fairfax, VA 22030

STAGE I PRE-SUBMISSION CONTACT

* All applicants must contact the Deputy Zoning Administrator-Plans at 703-385-7920 prior to submission of the site plan application and plans to discuss the proposed scope and filing requirements. **Projects are not accepted for review without the presubmission contact.**

STAGE II APPLICATION SUBMISSION

* Applications for site plan review that contain the following items with fees are acceptable for

Intake Processing:

- A. Site Plan Application
- B. Agent Letter (if applicant is not the property owner; also put on cover sheet)
- C. Submission Fee Worksheet
- D. Site Plan Checklist
- E. LEED Checklist
- F. Notification Letter Sample
- G. Water Quality Impact Assessment & Waiver Application
- H. Plans (with copy of signature block on cover sheet) (each submission 12 paper copies **and** "pdf" electronic format)
- I. VSMP package
- * Where applicable, any Special Exception, Variance and Special Use Permit approvals by City Council or the Board of Zoning Appeals must be obtained prior to site plan submission. The specific application requirements, forms and fees for these approvals are available from the City's website www.fairfaxva.gov or Zoning Division staff.

STAGE III SITE PLAN REVIEW

* Site plans are circulated to the plan review staff in the following City departments: Community Development and Planning, Public Works, Building Code/Fire Marshal, Real Estate and any other department that may need to provide staff review comments. First submission plans are forwarded to Fairfax Water for review.

- * Review comments are compiled by the Site Plan Coordinator and sent to the applicant's representative for consideration. The applicant's response (in letter format) to staff's comments must accompany all site plan resubmissions. Subsequent to first submission, the applicant shall work directly with Fairfax Water to obtain signature approval.
- * Architectural review and approval for building designs, landscaping and screening for all zoning districts except (single-family residences outside of the Old Town Fairfax Historic District and Transition District) and certain signage must be approved by the Board of Architectural Review.
- * Subdivisions may require preliminary and final subdivision plats to be approved by the Planning Commission or Director of Public Works prior to site plan approval. The specific application requirements, forms and fees for these approvals are available from the Zoning Division staff.
- * Building construction plans may be <u>submitted</u> to the Office of Building and Fire Code Administration for review and consultation with the Plan Review prior to site plan approval. **Applications for building permits will not receive Zoning compliance endorsement until the final site plan has been approved and bonding completed.**
- * Staff will notify the applicant's representative when signature submission of the site plan is authorized. Signature submission shall include a separate disc with the site plan and plat in "dxf" format for entry into the City's GIS database. (Additional information regarding "dxf" format is available from the City's GIS Analyst, 703.246.6331.)
- * Documents such as bond and site agreements, clearing and grading permits, tree removal permits, floodplain permit, stormwater detention/best management practices maintenance agreements, and siltation agreements and any associated fees may be submitted at any time. The approved sign plan will not be released until all the requirements of the Bond Submission package have been satisfied.
- * Building permits may be <u>issued</u> by the Office of Building and Fire Code Administration and street opening permits may be issued by the Department of Public Works **after the final site plan is approved and bonding is complete.**

STAGE IV CONSTRUCTION

- * A pre-construction meeting is required before ANY activity takes place on site. It is recommended that a preconstruction meeting be scheduled at least one (1) week in advance of planned start of any site activity. To schedule a preconstruction meeting, contact the Facilities Inspectors at 703-385-7828 and the Site Plan Coordinator at 703-385-7820. Failure to schedule a pre-construction meeting prior to site activity will result in a Stop Work Order by the Facilities Inspector and/or Building Code Inspector.
- * Written notices providing information to residents in the affected area (in most cases, one block from the construction activity) must be delivered one week before the beginning of construction activity and three days prior to any disturbance of utilities. The Facilities Inspector must be copied on all notices and a list of addresses that received notices must be provided.

- * Following a preconstruction meeting, limited clearing is allowed for installation of erosion and sediment controls.
- * Inspection of installed erosion and sediment controls and construction entrance is required before approval is given to begin land clearing activities.
- * Construction noise is allowed only between the hours of 7:00 AM and 6:00 PM on weekdays and 8:30 AM and 5:00 PM on Saturday **ONLY**. No construction noise is allowed during Sunday, evening/night hours and public holidays.
- * Work hours in the Right-of-Way are from 9:00 AM to 3:00 PM on weekdays, or as outlined in the approved ROW/Easement Permit.
- * Right-of-Way and On-Site Construction Inspection Fees are billed at the beginning of the project. A Right-of-Way/Easement Permit is required prior to starting work in any City Right-of-Way or Easement. Each road cut requires a separate traffic control plan for the particular work zone. Payment must be received for Right-of-Way and On-Site Construction Inspection Fees before a ROW/Easement Permit will be issued.
- * All site construction is monitored for adherence to requirements by the Facilities Inspector until the project is complete. Building construction is monitored by the Building Inspector from Code Administration.

STAGE V BOND ADMINISTRATION

- * To assist in completion of the remainder of this process, a Bonding Release package may be found on the City website (www.fairfaxva.gov).
- * Bond reductions may be requested as the project progresses up to 80% maximum reduction of the original site bond amount. A written request for bond reduction must be submitted on company letterhead, accompanied by completed amounts as certified on the City of Fairfax Surety Value Estimate form, and associated fees paid.
- * At the satisfactory completion of 80% of site improvements and/or within 30 days of the issuance of the permanent or temporary Certificate of Occupancy from the Office of Building and Fire Code Administration, an as-built plan, formal written request (on company letterhead) for release of the site and siltation bonds and associated fees must be submitted to the City Development Bond Administrator for agency review.
- * A temporary Residential or Non-Residential Use Permit may be issued to accommodate weather related delays for completion of **landscaping and paving only**.
- * After approval of the as-built plan, a two-year warranty bond must be submitted for approval with the associated surety review fee. The original site and siltation bonds will then be returned to the applicant.
- * A permanent Residential or Non-Residential Use Permit will be issued upon satisfactory compliance with all required improvements to provide safe public and emergency access.
- * Approximately three (3) months prior to warranty bond expiration, a letter from the City Development Bond Administrator will be mailed to the applicant; however this may be initiated by the bonding agent for the developer no sooner than three (3) months prior to

- warranty bond expiration.
- * The applicant will then be instructed to submit a formal request in writing (on company letterhead) for release of the warranty bond and pay the associated bond release fee. This request must be made prior to the expiration of the warranty bond.
- * Upon satisfactory inspection by the City Public Works Department Facilities Inspector, the original warranty bond will then be returned to the applicant.

VI CHANGES TO APPROVED SITE PLANS

- * Revisions to an approved site plan still under bond will be processed as a Site Plan Revision.
- * Final Design plans by Virginia Power for electric service must have City Staff authorization prior to installation.
- * Failure to obtain City approval of any changes or to install improvements and facilities according to the City approved plan may result in civil penalty fines and other legal remedies available to the City.

PAGE IS INTENTIONALLY LEFT BLANK



CITY OF FAIRFAX

Department of Community Development and Planning

SITE PLAN APPLICATION

□ Major	☐ Minor	☐ Amendment	☐ Revision to Bonded Site Plan
The following info	rmation is prov	vided, as required by the	e City of Fairfax Zoning Ordinance:
Project Name:			
Project Address: _			
Tax Map Number:			<u></u>
Property Owner :			
Address:			
Phone Number :			<u> </u>
E-mail address:			<u> </u>
Applicant:			
Address:			
Phone Number :			<u></u>
E-mail address:			
Engineer, Survey	or or Landsca	pe Architect:	
Address:			
Contact Person:		Pho:	ne Number:
E-mail address:			

THE SITE PLAN CHECKLIST MUST BE COMPLETED AND CERTIFIED BY THE APPLICANT'S ENGINEER

PAGE IS INTENTIONALLY LEFT BLANK

AGENT AUTHORIZATION STATEMENT

To Whom IT May Concern:	
I/We,	, the undersigned title owner(s) of the property
identified below do hereby authorize	of
	, to act as my/our agent(s) in the furtherance of an
application for a	
Tax Map No:	
Thank you in advance for your cooperation.	
Date:	By:
COMMONWEALTH/STATE OF:	
CITY/COUNTY:	,TO WIT:
The forgoing instrument was acknowledged befor	re me this day of
20, by	
	Notary Public (Signature)
AFFIX NOTARY SEAL/STAMP	Notary Registration No:
	My Commission Expires:

Date:	By:
COMMONWEALTH/STATE OF:	-
CITY/COUNTY:	,TO WIT:
The forgoing instrument was acknowledged	before me this day of
20, by	·
	Notary Public (Signature)
AFFIX NOTARY SEAL/STAMP	Notary Registration No:
	My Commission Expires:

	City of Fairfax APPROVED SITE PLAN
Director of	f Public Works Date
Review approval b	y:
	Fire Marshal (for water distribution system & fire hydrant location) Fairfax Water
	Director CDP
	Zoning Administrator
	City Engineer
	PW Plan Reviewer
	Code Admin. Asst. Chief
	Site Plan Coordinator
	BAR Liaison
	Environmental Reviewer
	Wastewater Reviewer
	GIS Manager
	Bonding Administrator Date

PAGE IS INTENTIONALLY LEFT BLANK

CITY OF FAIRFAX

Site Plan Checklist and Certification Statement

The following affidavit and checklist must be printed on the cover page and signed by a certified engineer, architect or land surveyor.

I the a	ttache	d site pl	Certification for Completeness and Accuracy do hereby certify that this site plan checklist is complete and an that is required pursuant to Section 110-101 thru Section 110-111 in the Code of		on of
(signat	ure)		(S)	EAL)	
pleas "Ren	e indio narks"	cate "N	Site Plan Checklist contain the following checklist information IN THE ORDER PRESCRIBED HER A" and explain in "Remarks" column. If an item is located on a different page than		pply
Yes	No	N/A	Description	Remarks	
			Engineer's name, address and phone number		
			Location map at a scale not less than 1"=2000', indicating scaled coordinates and		
			landmark information such as names of roads and water bodies.		
			Tax Map Number, Property Address, Project Name and Sheet Index		
			Seal and Signature of a professional engineer or other certified professional		
			Name and address of owner, developer and contract purchaser (if any).		
			Proposed floor area ratio and maximum permitted.		
			Area of parcel in square feet and acres		
			Deed book and page numbers		
			Disturbed area in square feet or acres		
			Number and type of dwelling units and allowed density (if applicable)		

			Number of parking and loading spaces required and proposed	
			Land use actions granted or requested for.	
			North arrow on all plan drawings and maps	
			Scale of each drawing, map or plan	
	$\{*\mathbf{I}$	Denote	s items that are required in digital format "dxf" for purpose of upda	ting the City's GIS data.}
CO	VER	PAGE	:	
Yes	No	N/A	Description	Remarks
			Date and preparation and revisions.	
			Proposed gross floor area and the area of the above grade horizontal surface of any	
			parking structure.	
			Landscaped open space required and proposed, zoning classification, use group	
			classification and type of construction(Uniform Statewide Building Code).	
			Certificate signed by the surveyor or engineer setting forth the source of title of the	
			Owner of the parcel(s) and the place of record of the last instrument in the chain of	
			Title.	
			Agent Authorization Statement (printed on plan cover sheet with signature)	
			City Signature Block	
NO	TES.	AND D	OCUMENTATION PAGE:	
Yes	No	N/A	Description	Remarks
			Documentation of approvals granted by City Council, Planning Commission,	
			Board of Zoning Appeals, Board of Architectural Review or any other agency.	

EXISTING CONDITIONS PAGE:

Yes	No	N/A	Description	Remarks
			Boundary of the entire property or properties.	
			Horizontal dimensions in feet and decimal fractions of a foot to the closest .00-foot	
			and all bearings in degrees, minutes, and seconds to the nearest 10 seconds.	
			Proof of easements required for the development.	
			Certified topographic map of the property at a two-foot contour interval, showing	
			existing contours and delineating the 100-year floodplain elevation.	
			USGS datum used for all deviations with location and elevation benchmarks.	
			(Should be NAD 83 for horizontal and NGVD29 for vertical).	-
			Locations and sizes of existing:	
			Fire lanes, "no parking", reserved parking and ADA parking.	
			Structures and their distance to property lines and center lines of adjacent streets.	
TEXT				
	1		DITIONS PAGE:	
Yes	STIN(No	G CON N/A	Description	Remarks
	1			Remarks
Yes	No	N/A	Description	Remarks
Yes	No	N/A	Description Public streets, sidewalks, bike trails and easements on and adjacent to the site	Remarks
Yes	No	N/A	Description Public streets, sidewalks, bike trails and easements on and adjacent to the site with rights-of-way, width of pavement, curbs, gutters, medians indicated,	Remarks
Yes	No	N/A □	Description Public streets, sidewalks, bike trails and easements on and adjacent to the site with rights-of-way, width of pavement, curbs, gutters, medians indicated, profiles, typical sections and pavement design.	Remarks
Yes	No	N/A □	Public streets, sidewalks, bike trails and easements on and adjacent to the site with rights-of-way, width of pavement, curbs, gutters, medians indicated, profiles, typical sections and pavement design. Driveways and curb cuts on the site and adjacent properties (indicate sight	Remarks
Yes	No	N/A	Description Public streets, sidewalks, bike trails and easements on and adjacent to the site with rights-of-way, width of pavement, curbs, gutters, medians indicated, profiles, typical sections and pavement design. Driveways and curb cuts on the site and adjacent properties (indicate sight distances for driveways entering public streets).	Remarks
Yes	No	N/A	Public streets, sidewalks, bike trails and easements on and adjacent to the site with rights-of-way, width of pavement, curbs, gutters, medians indicated, profiles, typical sections and pavement design. Driveways and curb cuts on the site and adjacent properties (indicate sight distances for driveways entering public streets). Parking and loading spaces, related driveways, walkways, drive-aisles and	Remarks
Yes	No	N/A	Public streets, sidewalks, bike trails and easements on and adjacent to the site with rights-of-way, width of pavement, curbs, gutters, medians indicated, profiles, typical sections and pavement design. Driveways and curb cuts on the site and adjacent properties (indicate sight distances for driveways entering public streets). Parking and loading spaces, related driveways, walkways, drive-aisles and pavement types.	Remarks

			Street and site lighting indicating all fixture styles, overall height, type of luminaire and footcandle and uniformity values.	
			Traffic controls.	
			Provisions for refuse disposal and recycling and required screening.	
			Stormwater management facilities including all structures (pipes, inlets, drains,	
			grates, etc) elevations, profiles, connections to existing facilities, ground clearance,	,
			detailed design of non-standard structures, calculations for pipe capacity, detention retention facilities and BMP's.	,
			Water and sanitary sewer facilities, including all structures (fire hydrants, meters,	
			manholes, etc.), sizes and types of pipes, elevations, profiles, ground clearance and	
			connections to public utility systems. (Indicate water pressure and flow capability,	
			static pressure, residual pressure and flow in gallons per minute)	
			Underground and overhead electric, telephone, cable, computer, gas lines and equipment.	
			Angles of bulk plane where minimum angles of bulk plane are controlled by	
			Zoning regulations.	
			Landscaping including a tree inventory with each tree's caliper size	
			labeled.	
CTT	ric di	AN PA	CE.	
Yes	No	N/A	Description	Remarks
			* Boundary of the entire property or properties.	
			Horizontal dimensions in feet and decimal fractions of a foot to the closest .00-	
			foot and all bearings in degrees, minutes, and seconds to the nearest 10 seconds.	
			Proof of easements required for the development.	
			Certified topographic map of the property at a two-foot contour interval, showing	
			existing and proposed contours and delineating the 100-year floodplain elevation.	

			USGS datum used for all deviations with location and elevation of benchmarks.	
			Proposed elevations at control points necessary to evaluate plan.	
			Locations and sizes of proposed:	
			Fire lanes, "no parking", reserved parking and ADA parking.	
			* Structures and their distance to property lines and center lines of adjacent streets.	
			* Public streets, sidewalks, bike trails and easements on and adjacent to the site with rights-of-way, width of pavement, curbs, gutters, medians indicated. Profiles, typical sections and pavement design.	
			* Driveways and curb cuts on the site and adjacent property (indicate sight distances for driveways entering public streets).	
			* Parking and loading spaces, related driveways, truck turning radius, walkways drive aisles and pavement types.	S,
			Recreation areas.	
			Fences, retaining walls and other similar structures, including an elevation drawing.	
			Guardrails, posts and other edge delineators.	
			Street and site lighting indicating all fixture styles, overall height, type of luminaire, and foot-candle and uniformity values.	
			Traffic controls and truck routes.	
			Provisions for refuse disposal and recycling, and required screening.	
	PLA	N PAG		
Yes	No	N/A	Description	Remarks
			Storm water management facilities including all structures (pipes, inlets, drains, grates, etc.) elevations, profiles, connections to existing facilities, ground clearance, detailed design of non-standard structures, calculations for pipe capacity, and detention facilities and/or BMPs must be shown on the Storm Water Management and Water Quality Plan pages.	

	* Water and sanitary sewer facilities, including all structures (fire hydrants, meters, manholes, etc.), sizes and types of pipes, elevations, profiles, ground clearance, and connections to public utility systems. Indicate water pressure and flow capability, static pressure, residual pressure, and flow in gallons per minute must be shown on the Utilities Plan Page (s).	
	* Underground and overhead electric, telephone, television, computer gas lines and equipment	
	Angles of bulk plane where minimum angles of bulk plane are controlled by zoning regulation.	
	Vertical cross-sectional view showing height of proposed structures, number of stories, location and access to underground parking, and proposed elevation of each floor, including basements.	
	Landscape materials, including a tree management proposal, showing existing and proposed vegetation with each tree's caliper size labeled.	

{*Denotes items that are required in digital format "dxf" for purpose of updating the City's GIS data.}

STORM WATER MANAGEMENT PLAN PAGE(S):

Yes	No	N/A	Description	Remarks
			Narrative: Contact information including the name, address, and telephone number of the owner and the tax reference number and parcel number of the property or properties affected	
			Description of current site conditions and final site conditions	
			Information on type and location of stormwater discharges	
			Information on the features to which stormwater is being discharged, including water bodies classified as impaired on the Virginia DEQ 303(d) list	
			Information on any additional control measures to be implemented to address a local TMDL	
			A general description of the proposed stormwater management facilities and the mechanism through which the facilities will be operated and maintained after construction is complete	
			Site Information:	
Yes	No	N/A	Description	Remarks
			Existing drainage facilities and creeks and channels, including all streams, ponds, culverts, ditches, wetlands, other water bodies, and floodplains	
			Soil types, geologic formations if karst features are present in the area, forest cover, and other vegetative areas	
			Current land use including existing structures, roads, and locations of known utilities and easements	
			Sufficient information on adjoining parcels to assess the impacts of stormwater from the site on these parcels	
			The limits of clearing and grading, and the proposed drainage patterns on the site	
			Proposed buildings, roads, parking areas, utilities, and stormwater management facilities	
			Proposed land use with tabulation of the percentage of surface area to be adapted to various uses, including but not limited to planned locations of utilities, roads, and easements	

Hydrologic Analysis: No N/A **Description Remarks** Yes *Pre-development and post-development contributing drainage areas Pre-development and post-development runoff rates, volumes, and velocities, and methodologies used Pollution load and reduction requirements and calculations П П П **Hydraulic Analysis:** N/A **Description Remarks** Yes No Sizing calculations for stormwater control measures П П П Existing and proposed structural elevations (pipe inverts, manholes, etc.) П П Stage-storage or outlet rating curves and inflow and outflow hydrographs for П П storage facilities Design water surface elevations П П П Analysis of potential downstream impacts/effects of the project П П П Location and elevation of the lowest floor in all proposed and existing buildings adjacent to the floodplain Dam safety and breach analysis П П П **Best Management Practices (BMPs):** Yes N/A Remarks No **Description** Type of facilities proposed (use BMP Clearinghouse names) Location, including geographic coordinates (Lat/Long) П П П Total acres treated П Acres impervious treated П П П Acres pervious treated Documentation and calculations verifying compliance with water quality and П П П quantity requirements

			Applicable supporting documents and studies (e.g., infiltration tests, geotechnical investigations	
			Landscaping plan for any BMPs or site reforestation	
{			tems that are required in digital format "dxf" for purpose of updati	ing the City's GIS data.}
X 7		ped Sy		Demonde
Yes	No	N/A □	Analyzed and designed for 2/10-yr/25-yr/100-yr Storm Primary road crossings designed for 25-yr flows and 10-yr under secondary roads and other locations	Remarks
			Culverts checked for the effects of 100-yr storm. No flooding of building structures shall result from 100-yr design flow	
			Energy dissipater calculations	
			Capacity of receiving channel downstream of channel or pipe system	
			Gutter spread limited to 10ft from the face of the curb	
			Hydraulic grade lines show 1ft below inlets	
(Inon (Chonn	el Systems:	
Yes	No	N/A	Description	Remarks
			Proposed channel capacity analyzed and designed for pre 10-yr storm	Teman no
			Channel designed for 2-yr Storm without erosion and 10-yr for bank fill (liner design)	
			Velocity Check (liners provided, if needed) Provide channel velocities.	
			Overlot grading plan.	
			Provide 100-yr overland relief assuming pipe system failure.	

CHESAPEAKE BAY REGULATIONS PLAN PAGE:

Yes	No	N/A	Description	Remarks			
			For any property depicted on the city's Chesapeake Bay preservation area map as				
			a resource protection area, applicant shall determine and show on the plan the				
			site-specific boundaries of the RPA components per code section 110-86(c). The applicant shall also submit a RPA site-specific study application available at				
			the Zoning Division or at:				
			http://www.fairfaxva.gov/cdp/docs/RPASiteSpecificStudyApplication.pdf				
			USACE jurisdictional determination or verification letter for RPA boundaries				
			Water quality impact assessment is required for any proposed development or				
			redevelopment unless the requirement is waived by the Zoning Administrator.				
			Application/waiver form is available at the Planning counter or at: http://www.fairfaxva.gov/cdp/docs/WQIAApplication.pdf				
П	П		Tree management plan per 110-86 (d).				
	_		Stormwater Management Plan				
Ц			BMP maintenance plan, including inspection schedule				
			BMP maintenance agreement (available at Planning counter)				
			Copies of any required wetland permits.				
Performance Standards of Chesapeake Bay Regulations:							
Yes	No	N/A	Description	Remarks			
			Maximize rainwater infiltration.				
			Reduce the land application of nutrients and toxics.				
			Minimize erosion and sedimentation potential.				
			Limit land disturbance and preserve indigenous vegetation to the maximum				
			extent practicable, consistent with the use or development proposed				

EROSION AND SEDIMENT CONTROL PLAN PAGE:

Yes	No	N/A	Description	Remarks
			An erosion and sediment control plan including: Limits of clearing and grading.	
Ш			Existing drainage patterns.	
			Critical erosion areas.	
			Locations of erosion and sediment controls and stormwater management practices to be used.	
			Any off-site land-disturbing activities.	
			Detail drawings of structures to be used.	
			A schedule of regular inspections and maintenance.	
			Erosion and sediment control narrative including descriptions of:	
Yes	No	N/A	Description	Remarks
			Project.	Kemarks
			Existing topography, vegetation and drainage	
			Show all off-site drainage areas that flow to or from the site.	
			Neighboring areas such as streams, lakes, residential areas, roads, and the like that might be affected by the land disturbance.	
			Any off-site land-disturbing activities.	
			Soils, including names, mapping unit, erodibility, permeability, depth, texture and soil structure.	
			Areas on the site that have potentially serious erosion problems.	
			Methods which will be used to control erosion and sedimentation.	
			Specifics regarding permanent stabilization of the site.	
			Increases in stormwater runoff and strategies to control runoff.	

			Design of temporary sediment basins, permanent stormwater detention basins, diversions, channels, and the like, including calculations supporting proposed design and for pre- and post-development runoff.	
			Maintenance plan for E&S control.	
			List minimum E&S standards 1 through 19 and how they are met.	
	_		PING PLAN PAGE:	T
Yes	No	N/A	Description	Remarks
			The following data in tabular form:	
			Tabulation of tree canopy on the site at 10-year maturity and minimum required.	
			Required number of landscaped parking islands.	
_			Buffer requirements- include fence detail and dumpster screening.	
	_			
			Planting plan with City details from PFM.	
			Planting plan with City details from PFM.	
			Planting plan with City details from PFM.	
			Planting plan with City details from PFM. E PLAN PAGE:	
				Remarks
	FIRE	E LANI	E PLAN PAGE: Description A fire protection plan including:	Remarks
	FIRE	E LANI	E PLAN PAGE: Description	Remarks
Yes	FIRE No	E LANI N/A	E PLAN PAGE: Description A fire protection plan including:	Remarks
Yes	FIRE No	E LANI N/A	E PLAN PAGE: Description A fire protection plan including: Location, width and radius of all existing and proposed fire lanes. Location of all fire lane signage. Location of all structures, denoting area, height, use group, construction type and	Remarks
Yes	FIRE No	E LANI N/A	E PLAN PAGE: Description A fire protection plan including: Location, width and radius of all existing and proposed fire lanes. Location of all fire lane signage. Location of all structures, denoting area, height, use group, construction type and sprinkler system if present.	Remarks
Yes	FIRE No	E LANI N/A	E PLAN PAGE: Description A fire protection plan including: Location, width and radius of all existing and proposed fire lanes. Location of all fire lane signage. Location of all structures, denoting area, height, use group, construction type and	Remarks
Yes	FIRE No	E LANI N/A	E PLAN PAGE: Description A fire protection plan including: Location, width and radius of all existing and proposed fire lanes. Location of all fire lane signage. Location of all structures, denoting area, height, use group, construction type and sprinkler system if present. Location of alarm annunciator, if present, and key repository. Location of all existing and proposed fire hydrants, including connection to water	Remarks
Yes	FIRE No	E LANI N/A	E PLAN PAGE: Description A fire protection plan including: Location, width and radius of all existing and proposed fire lanes. Location of all fire lane signage. Location of all structures, denoting area, height, use group, construction type and sprinkler system if present. Location of alarm annunciator, if present, and key repository. Location of all existing and proposed fire hydrants, including connection to water mains.	Remarks
Yes	FIRE No	E LANI N/A	E PLAN PAGE: Description A fire protection plan including: Location, width and radius of all existing and proposed fire lanes. Location of all fire lane signage. Location of all structures, denoting area, height, use group, construction type and sprinkler system if present. Location of alarm annunciator, if present, and key repository. Location of all existing and proposed fire hydrants, including connection to water	Remarks
Yes	FIRE No	E LANI N/A	E PLAN PAGE: Description A fire protection plan including: Location, width and radius of all existing and proposed fire lanes. Location of all fire lane signage. Location of all structures, denoting area, height, use group, construction type and sprinkler system if present. Location of alarm annunciator, if present, and key repository. Location of all existing and proposed fire hydrants, including connection to water mains. Location of all existing and proposed fire lanes and fire department connections	Remarks

PAGE IS INTENTIONALLY LEFT BLANK

CITY OF FAIRFAX NOTES TO BE INCLUDED ON THE SITE PLAN

PERMITS

- 1. A street opening permit is required for any work in a City right-of-way or easement. The permit can be obtained from the Public Works Department. For information, call 703.385.7980 or 703.385.7810.
- 2. All sidewalks, curbs, gutters, driveways, streets, storm pipes, sanitary sewer, endwalls and ripraps must be inspected by the City. All work in the City streets will be performed Monday-Friday between the hours of 9:00 a.m. and 3:00 p.m. No work is to be performed on weekends or holidays unless pre-approved by the Director of Public Works.
- 3. Inspections performed by the Facilities Inspector will require a four-hour notice prior to inspections.

GENERAL STANDARDS

- 1. The Public Works Director must be notified one week prior to pre-construction conference, one week prior to commencement of land disturbing activity and one week prior to final inspection. The Site Plan Coordinator in Zoning (703-385-7820) must be notified one week prior to the pre-construction conference.
- 2. A preconstruction meeting will be required three days prior to any construction. Contractors will notify the Public Works Department or Facilities Inspector for all work done on site and off site one day prior to starting.
- 3. The contractor shall provide adequate means for parking construction equipment and provide employee parking on site.
- 4. All construction shall conform to the latest City of Fairfax standards, Virginia Department of Transportation and the Virginia Sediment & Erosion Control current specifications, except as shown or altered by these plans.
- 5. Traffic signs found to be in the way at construction sites shall be removed or relocated only by personnel in the Sign & Signal Crew of the Public Works Department at the contractor's request. Any contractor found responsible for moving City property without permission will receive a summons.
- 6. All building construction shall be in accordance with the current edition of the Virginia Uniform Statewide Building Code. Permits and inspections for building, electrical, plumbing, mechanical and fire protection work are obtained from the Office of Code Administration, 703.385.7830.

- 7. Private fire mains require a permit from the Office of Code Administration. Permit application must include details of installation as specified in NFPA-24. An approved site plan is not a permit to install fire mains.
- 8. No portion of any building shall be occupied until a certificate of occupancy has been issued by the Building Official and a use permit by the Zoning Office.
- 9. No building, except additions or accessories to existing dwellings, shall proceed beyond first floor level until the location of the footing and walls as shown on a plat certified by a land surveyor has been approved by the Zoning Administrator.
- 10. An as-built plan must be submitted within 30 days after completion of all construction.
- 11. Temporary structures, construction trailers and demolition require permits from the Office of Code Administration prior to start of work or installation.
- 12. Adequate emergency vehicle access shall be maintained at all times. A hard surfaced, all-weather roadway shall be provided to within 50 feet of all structures and any location where combustible materials are stored.
- 13. City ordinance permits construction noise, including excavation, between the hours of 7:00 am and 6:00 pm on weekdays and 8:30 am and 5:00 pm on Saturdays ONLY. It shall be the responsibility of the developer to ensure that all contractors and subcontractors comply with this ordinance.
- 14. The Developer shall be responsible for ensuring compliance with City Code sections limiting growth of grass and weeds to six inches in height.

CONSTRUCTION

- 1. All subgrade and sub-base material shall be compacted to 95% of theoretical maximum density as determined by A.A.S.H.O. T-99 method A within plus or minus 20% of optimum moisture for the full width of any dedicated right-of-way and all townhouse, apartment, condominium, commercial and industrial parking lots (including storm sewer and sanitary sewer).
- 2. Compaction test shall be performed by the contractor. Subgrade for curb, gutter and sidewalk shall be every 50 feet; sub-base will be alternated every 25 feet. Driveways require two tests on subgrade and sub-base. Copy of results is required prior to placing any type of material. VTM-1 correction also must be used. All structures require two tests on subgrade and sub-base.

- 3. Compaction tests for roadways shall be performed by the City only, unless approved by the Public Works Director. Compaction tests for all building pads must be submitted to the office of Code Administration for review and approval.
- 4. All underground utilities within the street right-of-way shall be installed to the required distance beyond the right-of-way.
- 5. Storm sewer and culvert pipe shall be reinforced concrete pipe to conform to the current A.A.S.H.T.O. designation M170, unless otherwise designated on the plans. Class II pipe is permitted beyond the limits of street rights-of-way. Class III pipe is required within the limits of the rights-of way.
- 6. All curb and gutter shown on plans and not in profiles shall be on straight tangent grades. The contractor shall round all vertical breaks with smooth spline curbs.
- 7. All pavement placed on City right-of-way shall have a mix design approved prior to placing material and a density test performed during placement.
- 8. Street signs and markings shall be installed by the developer at all street intersections in a location to be determined by the Director of Public Works. Private access ways and alleys shall be clearly designated as such by a sign at every entrance from a public street, stating "private street, privately owned and privately maintained". All street markings and signage will conform to City of Fairfax standards and the Manual of Uniform Traffic Control, per the Street Superintendent.
- 9. C.B.R. test is required for actual determination of required sub-base thickness prior to construction. Depth of sub-base is based on subgrade C.B.R. value of 10. Where C.B.R. value is less than 10, one-inch of sub-base or base material shall be added for each point below 10 for on-site and off-site and shall be reviewed by the City of Fairfax for special design.
- 10. All construction must comply to the Code of Virginia 36-98 and 36-99 by reference as part of the Uniform Statewide Building Code of Virginia, the final fair housing accessibility guidelines (24 CFR Chapter I) and the Americans with Disabilities Act accessibility guidelines (28 CFR, part 36) as per site and right-of-way work compliance.
- 11. Provide proper distance from back of sidewalk to building for stoops and steps, and the like.
- 12. All roofs, paved areas, yards, courts and courtyards shall be drained into a separate storm sewer or a combined sewer system.

ENVIRONMENTAL

- 1. All erosion siltation control to be installed prior to starting project to conform to the current Virginia Erosion and Sediment Control Manual.
- 2. The contractor shall provide adequate means of cleaning mud from trucks and/or other equipment prior to entering the City of Fairfax rights-of-way. It is the contractor's responsibility to clean streets and allay dust and to take whatever measures necessary to ensure that the road is maintained in a clean and dust-free condition at all times.
- 3. It shall be the contractor's responsibility to perform the work in such a manner to prevent the washing of any topsoil, silt, or debris onto adjacent properties.
- 4. If the presence of asbestos is suspected in the soil, the contractor must contact the Air Pollution Control Division of the Fairfax County Health Department at 703.246.2300.
- 5. Onsite storage of fuel shall be limited to diesel fuel tanks not over 660 gallons capacity. Tanks shall be of a listed type and shall be provided with approved secondary containment, impact protection and placarding. A minimum 2A-40BC fire extinguisher shall be provided in the vicinity of the refueling area. A permit for combustible liquid storage shall be obtained from the Office of Code Administration, 703.385.7830. Fuel shall not be placed in onsite storage tanks until the installation has been inspected and approved.
- 6. Onsite repair of vehicles and equipment shall be limited to replacement of damaged belts, hoses and tires. Any spill of fuel, oil, hydraulic fluid or anti-freeze greater than one gallon must be reported to the Office of Code Administration at 703.385.7830. All spills must be cleaned up promptly and in an approved manner.
- 7. The Owner shall be responsible for ensuring compliance with City Code sections regarding health and safety menaces, including accumulations of water, storage of material, construction debris and security of the site.
- 8. The link to the asbestos information and map on the Fairfax County website http://www.fairfaxcounty.gov/hd/asb/
- 9. Prior to the start of any site grading work, the developer or owner shall obtain a Virginia Stormwater Management Program (VSMP) permit from the City of Fairfax. The VSMP permit requires that a Stormwater Pollution Prevention Plan (SWPPP) be kept at the construction site at all times.

LANDSCAPE

- 1. The area surrounding all trees, shrubs and groundcover shall be topped with two inches of shredded hardwood bark mulch.
- 2. No changes shall be permitted to the plant list unless approved by the City of Fairfax.

 Department of Community Development and Planning

 City of Fairfax, Virginia

- 3. Trees shall be classified as per "American Standard for Nursery Stock" as adopted by the American Association of Nurserymen. Plant material below this standard shall not be considered.
 - a) All plants must conform to requirements per plant list;
 - b) All plant materials must be nursery grown stock;
 - c) All trees must be well branched, full crown.
- 4. At least 5 days before being planted, the Site Plan Coordinator shall be notified that plants are available for inspection.
- 5. No person shall remove or destroy any tree which is five (5) inches or greater in caliper, measured six (6) inches above ground level, on any lot greater than one-half (1/2) acre without first obtaining a tree removal permit from the Zoning Administrator. Any tree removed, damaged or destroyed will be replaced at the discretion of the Zoning Administrator.

DEPARTMENT OF PUBLIC WORKS SANITARY SEWER STANDARD NOTES GENERAL

- 1. All sanitary sewers shall be constructed in accordance with the current City of Fairfax Standards and Specifications.
- 2. Easements for all sanitary shall be 10' unless otherwise noted.
- 3. Sanitary sewers and water mains shall maintain a minimum of 15' horizontal separation from proposed or existing buildings.
- 4. No landscaping or other utilities (i.e. gas, phone, cable, etc.) are permitted in the sewer easements, except at crossings.
- 5. Contractor shall request pre-construction meeting and inspection by the City of Fairfax Department of Public Works (703.385.7810) three days prior to commencing construction of any sewer mains.
- 6. A permit for installation of sanitary sewers and fire hydrants shall be obtained from the Department of Public Works.
- 7. Sewer laterals not within an easement require plumbing permits and inspections from the Office of Code Administration. The inclusion of these items does not constitute a permit.

SANITARY SEWER:

- 1. Sanitary sewers shall be PVC DR-25 per AWWA C-900, unless otherwise noted.
- 2. Sanitary sewer laterals shall be 4" PVC DR-25 between the main and the property line and shall enter the main at 90 degrees. A cleanout shall be installed at the property line.
- 3. A 2" detectable metal marking tape shall be placed 3-feet above all sanitary sewers.
- 4. The Department of Public Works shall inspect sanitary sewers by a camera after the lines are put in service.
- 5. Finish grade shall drain away from manholes located outside of pavement areas.
- 6. Top of manholes located outside of pavement areas shall be 3" above final grade, except in established lawns where it shall match the final grade.
- 7. Manholes shall have bituminous coating on the outside walls.
- 8. All sanitary manhole lids shall be heavy duty and shall have the words "Fairfax City Sewer" cast in them.
- 9. Drop manholes shall have an 8" inside drop pipe.
- 10. Manholes in 100 yr. Flood plain shall have watertight lids.
- 11. All testing is provided by the contractor, as directed by the city inspector.



CITY OF FAIRFAX NOTES TO BE INCLUDED ON THE SITE PLAN

NOTES TO BE INCLUDED ON RESIDENTIAL PLANS

No building shall proceed beyond the first floor level until the horizontal location and elevation of the top of each foundation wall as shown by certified surveyor's plat thereof, has been approved by the Zoning Administrator.

It shall be the developers and/or owners responsibility to perform the work in such a manner to prevent the washing of topsoil, silt, or debris onto adjacent properties.

It shall be unlawful for any person to engage in land disturbing activities of two thousand five hundred (2,500) square feet or more for any purpose until a permit is issued by the plan-approving authority.

All Erosion Control to be installed prior to starting project to conform to the current Virginia Erosion Control Manual.

A street opening permit is required for any work in the City right-of-way or easement. The permit can be obtained from the Public Works Department. For information call 385-7983 or 385-7828.

All on-site utilities shall be installed underground in accordance with city and applicable utility company standards.

No portion of the building shall be occupied until a Residential Use Permit has been issued by the Zoning Administrator.

The developer shall provide adequate means of cleaning mud from trucks and/or equipment prior to entering the City of Fairfax rights-of-way. It is the developers responsibility to clean streets and to take measures necessary to ensure that the road is maintained in clean and dust-free condition at all times.

The developer shall provide for adequate storm drainage so that the proposed improvement of the property does not direct concentrated flow to adjoining properties. The drainage shall be approved by the City Building Inspector and Facilities Inspector prior to issuing the occupancy permit.

Each development shall provide for the planting or retention of trees on the site to the extent that, at a maturity of ten years, the minimum lot coverage shall be twenty (20) percent for a site zoned R-2, R-3, RT-6, RT or any other residential site zoned three (3) to ten (10) units per acre.

Any application proposing to remove or destroy existing trees in conjunction with any land development activity shall submit a tree management plan containing such information as deemed necessary by the zoning administrator (Sec. 110-252).

PAGE IS INTENTIONALLY LEFT BLANK



CITY OF FAIRFAX SITE PLAN REVIEW FEE CALCULATION SHEET

Project Name:		Site Plan #	
<u>Category</u>		eview Fees (# 316462) Measurements	<u>Fee</u>
Base Fee \$6,600 (ma	ajor); 2,750 (minor); 1,10	0 (amendment)	
Second and Subsec	quent Revision \$550 eac	ch additional submission	
Bituminous Surface	\$0.44/sq.yd.		
Sidewalk	\$0.77/lin.ft.		
Curb & Gutter	\$0.77/lin.ft.		
Header Curb	\$0.77/lin.ft.		
Storm Drainage	\$3.85/lin.ft.		
Sanitary Sewer	\$2.00/lin.ft.		
Water	\$2.00/lin.ft.		
Required Screening	\$2.00/lin.ft.		
Overlot Grading	\$220 per division of land or disturbed acre or fraction thereof (whicher	ver is greater); plus \$100 per inspection of	conducted by the Dept. of
	Public Works		
Tree Management	\$110 per division of land or disturbed acre or fraction thereof (whichev		
Water Quality Impac Assessment Review (\$110 per individual	\$330		
Site Plan Review F	ee Total		

FEES:

Erosion & Sedime	ent Plan Review (#3	13310)			
Base fee of \$550.00	up to ½ acre of distu	urbed land,	Acre:	Fee:\$	
Includes 1 site insp	pection; each additio	onal inspection	n is \$100.00		
Base fee of \$550.00) plus \$100.00 per ac	re or fraction tl	nereof, Acres:	Fee:\$	
Includes 1 inspe	ection, each additiona	al inspection is	\$100.00		
Reinspection fo	ollowing violation @	\$200.00; \$300	. if a stop work orde	r has been issued (per inspectio	n)
After-Hours Ins	spection fee @\$200.0	00 minimum up	to 4 hours		
Overtime Relat	ed to Inspections @	150.00			
Rescheduling for	ee for site inspection	\$45.00			
RPA delineatio	n/determination \$275	5.00			
Surety Review (#3: Performance bond, 1 Less than \$100,000 \$100,001-300,000 > \$300,000 Request for reduction Request for replacer	letter of credit, cash e \$275.00 each \$550.00 each \$800.00 each	\$275.00 ea \$275.00 ea			
		TOTAL I	REVIEW FEE:		
Fee computed by: _		Name and T	itle	_Date	

*Please review City fee schedule for additional fees that may apply to your project.

CITY OF FAIRFAX SITE PLAN REVIEW NOTIFICATION

The Zoning Office requires the applicant to notify by certified mail the owners of each property abutting or across the street from the subject property informing them that the site plan has been submitted and will be considered for approval not less than ten days after receipt of notice.

S	A	٨	IPI	\mathbf{E}	N	O	TI	CE:	
D.	$\overline{}$	T.A		1	_ 1 ⊿	`		· LL	

Date

Dear Property Owner:

Pursuant to Section 110-102(e) of the City of Fairfax Zoning Ordinance, you are hereby notified that a site plan has been submitted to the Zoning Office for consideration.

You are invited to review this site plan in the Zoning Office, Room 207, City Hall. Should you have any objections to this plan, you must file your objections, in writing, with the Zoning Office within ten days after receipt of this notice.

Site Plan name and number Type of use Address

Applicant's signature and address

cc: Zoning Administrator/Case Manager

Department Of Community Development and Planning

Water Quality Impact Assessment (WQIA) and Waiver Application

The Water Quality Impact Assessment requirements are described on the following pages. Please review these requirements, compute your WQIA calculations (or waiver request) and complete the application provided with these instructions. The request to waive the requirement for a WQIA can be made by completing Section II.

Submit the completed application, WQIA calculations (or waiver request) and review fee along with the site plan application and fees to the Department of Community Development and Planning, Zoning Division.

WQIA review fees: \$110 per individual residential lot or \$330 for other development Account #316462

Project Name:	
Project Address:	
Tax Map Number:	
Property Owner:	
Address:	
E-mail:	
Applicant (If different from Owner):	
Address:	
E-mail:	
Engineer:	
Address:	Phone:
Land Surveyor (if different):	
Address:	Phone:
Wetlands Expert (if different):	
Address:	Phone:

The Water Quality Impact Assessment is conducted to identify the impacts of proposed development on water quality and lands within resource protection and resource management areas; to ensure that where development does take place it is located on those portions of a site and in a manner that is least disruptive to the natural functions of the land and to specify mitigation measures to address water quality protection.

The applicant shall submit a WQIA in accordance with Section 110-85(b) for:

- 1. Any proposed land disturbance, development or redevelopment within a resource protection area including any buffer area modification or reduction as provided for in section 110-84; or
- 2. Any proposed development or redevelopment in the resource management area that may significantly impact water quality due to the unique characteristics of the site or intensity of the proposed use or development.
- 3. Upon determination that the proposed development or redevelopment would not significantly impact water quality, the zoning administrator may waive this requirement as stated in subsection 110-80(e).

I. Development Characteristics

You must submit either a minor or major WQIA for your project unless you receive a waiver. The below conditions will determine whether you submit a major or minor WQIA.

Submit a Minor WQIA if you answer "Yes" to either of these development characteristics (Section 110-85(c)):

______ 5,000 square feet of disturbance or less

_____ Encroachment onto the landward 50 feet of the 100-foot buffer area

(Skip to Section III, Minor WQIA Requirements)

Submit a Major WQIA if you answer "Yes" to any of these development characteristics (Section 110-85(d)):

_____ Over 5,000 square feet of disturbance

_____ Encroachment onto the seaward 50 feet of the 100-foot RPA buffer area

_____ Location in the resource management area and is deemed necessary by the Zoning Administrator.

(Skip to Section IV, Major WQIA Requirements)

II. WQIA Waivers

_____ Check here if you plan to submit a WQIA waiver request.

To submit a WQIA waiver request, attach a report detailing how the proposed development or redevelopment does not significantly impact water quality.

III. Minor WQIA Requirements (Section 110-85(c))

The minor WQIA calculations will demonstrate that the remaining buffer area and best management practices will result in removal of no less than 75 percent of sediments and 40 percent of nutrients from post development stormwater runoff.

Requirements for a minor WQIA scaled site drawing include:

- 1) Location of the components of any RPA, including the 100 foot buffer area;
- 2) Location and nature of proposed improvements, including:
 - a. Type of paving material;
 - b. Areas of clearing or grading;
 - c. Location of any structures, drives, or other impervious cover; and
 - d. Sewage disposal systems or reserve drain field sites;
- 3) Type and location of proposed best management practices to meet the required general performance standards specified in Section 110-84;
- Location of existing vegetation on site, including the number and type of trees and other vegetation to be removed to accommodate the encroachment or modification; and
- 5) A re-vegetation plan that supplements the existing buffer vegetation in a manner that provides for pollutant removal, erosion and runoff control.
- 6) Certification of all required information as complete and accurate by a professional engineer, land surveyor, landscape architect, soil scientist, or wetland delineator certified or licensed to practice in the Commonwealth of Virginia.
- 7) RPA boundaries shall include a jurisdictional determination or verification letter from the U.S. Army Corps of Engineers for all Waters of the U.S.

IV. Major WQIA Requirements (Section 110-85(d))

Requirements for a major WQIA include:

- 1) All of the information required in a minor WQIA (Section III above);
- 2) Hydrological element that describes:
 - a. Existing topography;
 - b. Estimates of soil characteristics and potential for erosion;
 - c. Hydrology of the area;
 - d. Impacts on wetlands and streams;
 - e. Proposed mitigation measures; and
 - f. Listing of requisite permits with permit or application status.

3) Landscape element that describes:

- a. Existing trees required to be identified as part of a Tree Management Plan in accordance with subsection 110-252(c);
- b. Limits of clearing and grading;
- c. Trees and indigenous vegetation that are to be preserved within the disturbed area;
- d. Measures to be taken to protect vegetation, proposed plantings and other vegetative measures used to enhance water quality; and
- e. Proposed construction schedule that includes all activities related to clearing, grading and proposed plantings.
- 4) Such other measures as deemed necessary by the Zoning Administrator to ensure the impact to water quality can be accurately predicted;
- 5) Certification of all required information as complete and accurate by a professional engineer, land surveyor, landscape architect, soil scientist, or wetland delineator certified or licensed to practice in the Commonwealth of Virginia; and
- 6) RPA boundaries shall include a jurisdictional determination or verification letter from the U.S. Army Corps of Engineers for all Waters of the U.S.

V. <u>Evaluation Procedure (Section 110-85(f))</u>

Minor WQIA

The Zoning Administrator shall determine if any proposed modification or reduction to the buffer area is consistent with the provisions of this division and make a finding based upon the following criteria:

110-85(f)1.	Minor WQIA Criteria	Satisfied (Y/N)
a.	The proposed encroachment is necessary and	
	there is no other location on site to place	
	improvements without disturbing the buffer	
	area.	
b.	The impervious surface is minimized.	
C.	The proposed best management practices,	
	where required, achieve the requisite reductions	
	in pollutant loadings.	
d.	The development, as proposed, meets the	
	purpose and intent of this division.	
e.	The cumulative impact of the proposed	
	development, when considered in relation to	
	other development in the vicinity, both existing	
	and proposed, will not result in a significant	
	degradation of water quality.	
f.	Any other information deemed necessary by the	
	Zoning Administrator.	

Major WQIA

The Zoning Administrator shall determine if the proposed development is consistent with the purpose and intent of this division and make a finding based upon the following criteria:

110-85(f)2	Major Water Quality Criteria	Satisfied (Y/N)
a.	The disturbance of any wetlands is minimized.	
b.	The development will not result in significant	
	disruption of the hydrology of the site.	
c.	The development will not result in significant	
	degradation to aquatic life.	
d.	The development will not result in unnecessary	
	destruction of plant materials on site.	
e.	Proposed erosion and sediment control	
	concepts are adequate to achieve the reductions	
	in runoff and prevent offsite sedimentation.	
f.	Proposed stormwater management measures	
	are adequate to control the stormwater runoff	
	to achieve the required performance standard	
	for pollutant control.	
g.	Proposed revegetation of disturbed areas will	
	provide optimum erosion and sediment control	
	benefits.	
h.	The design and location of any proposed drain	
	field will be in accordance with the general	
	performance standards outlined in section 110-	
i.	84.	
1.	The development, as proposed, is consistent	
:	with the purpose and intent of this division.	
j.	The cumulative impact of the proposed	
	development, when considered in relation to	
	other development in the vicinity, both existing	
	and proposed, will not result in a significant	
	degradation of water quality.	

	degradation of water quality.	
WOLA Appro	ved/ Waiver Approved	Date
w QIA Applo		Date
	Special Projects Engineer	



10455 Armstrong Street, Room 207A Fairfax, VA 22030 **Phone: 703-385-7820 Fax: 703-385-7824**

TREE REMOVAL PERMIT APPLICATION Account #316464

<u>FEES:</u> Individual Residential Lot \$10.00 / Residential Development Project \$100.00 / Other \$50.00 (Commercial)

Tax Map No.:		Pentamation Case #:Permit No:
City of Fairfax Code Section	n 110-252(a) Permit Requi	red:
inches above ground level, or permit from the Zoning Adm	n any lot larger than one-ho inistrator in accordance wi stroy any such tree located	e (5) inches or greater in caliper, measured six (6) alf ($^{1}\!\!/_{2}$) acre without first obtaining a tree removal th the procedures set forth in this division. Further in the common open space of any development
Name of Applicant:		
Address of Applicant:		
Telephone Number:		
Person or Firm Removing		
The following information is property Address:	•	
Number of Trees:		
Location of Tree(s):		
, ,		
, ,		
Reason for Removal:		
I,(Print Name) removal of any tree(s) covered		full responsibility for damage caused by the
•	•	(Signature)
I,		/owner's agent agree to this application for Tree
Removal Permit.		
(Signature)	(Phone Number)	(Date)
(Address)		

Department of Community Development and Planning City of Fairfax, Virginia



10455 Armstrong Street, Room 207A Fairfax VA 22030

Phone: 703-385-7820 Fax: 703-385-7824

A Tree Management Plan must be submitted for any land development activity and for any tree removal project as requested by the Zoning Administrator.

VIOLATIONS AND PENALTIES City of Fairfax Code Section 110 -9(c)(1):

Any person, whether owner, lessee, principal, agent, employee or otherwise who commits, permits, assists in or attempts any violation of the following provisions, whether by act or omission, shall be punishable by a civil penalty of \$200.00 for the initial violation and \$500.00 for each additional violation of the same Code section.

City of Fairfax Code Section 110-253 (Acts harmful to trees):

- a. No person shall abuse, mutilate or otherwise damage any tree located on public property, or any tree protected by section 110-253, including those located in the public right-of-way along street frontages within subdivisions. However, nothing in this division shall be construed to prevent reasonable and proper trimming of trees located on public property by authorized persons in accordance with accepted horticultural practices.
- b. No person shall attach any sign, notice, placard, electrical wire or other injurious device to any tree, nor shall any person cause any substance harmful to trees to come in contact with them, or prevent water and oxygen from reaching their roots.
- c. No person shall cover the ground with impervious material any closer to the trunk of a tree than its dripline. This provision may be waived by the zoning administrator if he determines that the proposed action will not harm the tree.

REMOVAL OF VEGETATION IN RPA COULD RESULT IN ADDITIONAL PENALTIES AND FINES City of Fairfax Code Section 110-84(b)(2) (Development and redevelopment in Chesapeake Bay preservation areas):

Indigenous vegetation shall be preserved to the maximum extent practicable consistent with the use and development proposed and in accordance with the "Virginia Erosion and Sediment Control Handbook."

- a. Existing trees shall be preserved outside the limits of disturbance; however, diseased trees or trees weakened by age, storm, fire or other injury may be removed.
- b. Clearing and grading shall be limited outside the defined limits of disturbance. Clearing shall be allowed only to provide public roads, necessary access, positive site drainage, water quality BMPs, and the installation of utilities, as approved by the zoning administrator.
- c. Prior to clearing or grading, suitable protective barriers, such as safety fencing, shall be erected at the drip line of any tree or stand of trees to be preserved. These protective barriers shall remain so erected throughout all phases of construction. The storage of equipment, materials, debris, or fill shall not be permitted within the area protected by the barrier.

BAR APPROVAL Proposal meets design criteria of section 110-958 per section 110-1075: Circle one: YES / NO			
Approved by BAR:		Date:	
Approved by:		_Date:	
Fee Paid:	Receipt No.	Date:	



G.P#	
------	--

10455 Armstrong Street, Fairfax, VA 22030 Community Development and Planning Phone: 703-385-7820 Fax: 703-385-7824

Grading, Filling or Excavating Permit Account # 313310

Major (PW Director approval required for Minor (Zoning Administrator approval red		D – Fee and Bond)
Development Name/Location:		
Dimension of area: Dept	th of Area:	
Reason:		
What will be done with the disturbed/displaced	d land:	
AUTH	ORIZATION STATE	EMENT
Pursuant to City Code Sections 110-338 and 110 (Director/Administrator) has the right and po	0-339 and insofar as the Dower, PERMISSION is 1	Pirector of Public Works/Zoning Administrator
grade, fill, excavate, remove or destruct a portion approved (check one) Erosion and Sediment attached sketch.	of the natural topsoil or t	rees or other vegetative cover as shown on the
Said major or minor grading, filling and ex- Director/Administrator as inspected by the City's discretion, complete the major work at the exper- penalty fines for major and minor work not comp municipal control over the subject matter of this pe	Site/Facilities Inspector, a nse of the applicant. The Appleted according to the appleted accord	nd if not so completed the Director may, at its Administrator may, at its discretion, issue civil
Receipt acknowledges payment to the Treasurer, C fee) and \$ (Performance Bond) to No fee or bond required for minor work.		
Approval Date:	Time Limit Expiration	
By: Director/Administrator ACKNO	OWI EDCEMENT ST	'ATEMENT
This permit is accepted and understood to be limite following signatures:		
Property Owner Name:	Signature:	
Address:		Zip Code
Contractor Name:	Signature:	
Address:		Zip Code

Note: THIS PERMIT MUST BE KEPT ON THE WORK SITE AND SHOWN WHEN REQUESTED. This permit becomes invalid upon expiration of the time limit. An extension of time may be requested if the work is underway but not completed.



SITE PLAN ORDINANCE

Below is a copy of the Site Plan Ordinance, which is an excerpt of Chapter 110 of the City Code. Chapter 110 contains the City's zoning regulations and the applicant is responsible for knowledge of all zoning regulations applicable to the proposed development. Copies of Chapter 110 in its entirety can be purchased from the Zoning Office, Room 101, City Hall.

DIVISION 4. SITE PLANS¹

Section 110-101. Development of land use requiring a site plan.

- (a) A site plan is required for any use or development of property located in any zoning district, except:
 - (l) Single-family detached dwellings, related accessory structures and any special use not requiring physical alterations to the lot or building.
 - (2) Temporary public uses which do not exceed thirty (30) days in duration.
- (b) No building permit or certificate of occupancy shall be issued for a development requiring a site plan until the site plan has been approved.

Section 110-102. Procedure

- (a) All site plans which are appropriately submitted and conform to the standards and requirements set forth in this chapter shall be approved by the plan approving agent designated by the city manager, hereafter referred to as the agent.
- (b) The property owner or his designee shall submit to the zoning administrator a completed application and twelve (12) prints of the site plan.
- (c) Site plans shall be prepared and certified by an engineer, architect, land surveyor or landscape architect duly authorized to practice by the Commonwealth of Virginia. No person shall prepare or certify any portion of a site plan which is outside the limits of his professional expertise and license.

¹ Editor's note: Ord. No. 1986-29, adopted June 24, 1986 amended Div. 4 in its entirety to read as herein set forth. Prior to such amendment, Div. 4, consisting of Sections 26-20--26-28 and 26-30, pertained to similar subject matter and was derived from: ordinance of Dec. 7, 1960, Section 3; ordinance of Dec. 2, 1969; ordinance of Feb. 5, 1974; Ord. No. 1975-14, adopted April 8, 1975; Ord. No. 1978-2; Ord. No. 1980-13, Section 2, adopted July 15, 1980; Ord. No. 1984-10, adopted Sept. 11, 1984; and Ord. No. 1984-27, adopted Dec. 18, 1984.

- (d) Site plans shall be prepared at a scale of not less than one (l) inch equals fifty (50) feet and shall be submitted as twenty-four (24) by thirty-six (36) inch blue or black line copies unless excepted by the agent. Each site plan shall contain all information required by this chapter.
- (e) With the site plan, the applicant shall submit applicable fees consistent with the adopted fee schedule and certified mail receipts from notices sent to the owners of each property abutting or across the street from the subject property informing them that the site plan has been submitted and will be considered for approval not less than ten (10) days after receipt of the notice. If the adjacent development is of condominium ownership, then notification sent to the condominium association shall be sufficient to satisfy this provision.
- (f) Written comments pertaining to a site plan may be filed with the zoning administrator by any interested party within the period prescribed in the notice.
- (g) The site plan shall be forwarded to the board of architectural review pursuant to section 110-1072 if the subject site is located in the Old and Historic District.
- (h) The agent shall notify the applicant in writing of the action to approve or deny the site plan and shall forward a copy to the zoning administrator. In the event that a site plan is denied, the agent shall indicate the reasons for denial. The agent's decision may be appealed to the board of zoning appeals in accordance with section 110-1105 et seq. (Ord. No. 1986-29, 6-24-86)

Section 110-103. Required information.

All site plans shall contain the following information:

- (1) Location of tract by an insert map at a scale of not less than one inch equals two thousand feet (I" = 2000'), indicating scaled coordinates referred to in U.S.C.& G.S., state grid north and such information as the names and numbers of adjoining roads, streams and bodies of water, railroads, subdivisions, towns, and districts or other landmarks sufficient to clearly identify the location of the property.
- (2) Name and address of the owner or developer and contract purchaser (if any), north point, scale of the drawing and date of preparation and revisions.
- (3) Boundary of the entire tract by courses and distances with reference to true meridian or state grid system and area of the tract.
- (4) All horizontal dimensions shown on the site plan shall be in feet and decimal fractions of a foot to the closest one hundredth of a foot (.00), and all bearings in degrees, minutes and seconds to the nearest ten (10) seconds.
- (5) Certificate signed by the surveyor or engineer setting forth the source of title of the owner of the tract and the place of record of the last instrument in the chain of title.

Department of Community Development and Planning City of Fairfax, Virginia

- (6) Certified topographic map of the parcel at a minimum two-foot contour interval, showing existing and proposed contours and delineating the one-hundred-year floodplain elevation, if applicable.
- (7) USGS datum used for all elevations with location and elevation of benchmark shown.
- (8) Locations and dimensions of existing and proposed:
 - (a) Structures on the site showing distance to lot lines and centerlines of adjacent streets;
 - (b) Streets and easements on and adjacent to the site with rights-of-way and pavement widths;
 - (c) Driveways and curb cuts on the site and adjacent properties;
 - (d) Parking and loading areas; all off-street parking, related driveways, loading spaces and walkways, indicating type of surfacing, size, angle of stalls, width of aisles and location, height and intensity of proposed lighting;
 - (e) Sidewalks, trails and open space;
 - (f) Median strip openings and their relationship to the site:
 - (g) Water and sanitary sewer facilities, indicating all pipe sizes, types, and grades and the location of connection to public utility systems;
 - (h) Underground electric, telephone and television cables, both on-site and in adjacent rights-of-way.
 - (i) Street and site lighting, indicting all fixture styles and heights, types of luminaire, location of fixtures, and foot candle and uniformity values.
- (9) Proposed elevations at control points such as driveways, ramps and any other locations determined by the agent to be necessary for the adequate evaluation of the plan.
- (10) The proposed location and general use of each building, including outside display areas.
- (11) Angles of bulk plane where minimum angles of bulk plane are prescribed by the provisions of this chapter.
- (12) Sufficient information to show how the physical improvements associated with the proposed development such as walkways, driving lanes, and curb and gutter interrelate with existing or proposed development of record on adjacent properties.

- (13) A tree management plan as required in Division 10 and a landscaping plan showing the location, number, type and size of all proposed plant material at the planting and maturity stages. The landscaping plan shall also depict all trees existing on-site prior to development which are larger than five (5) inches in diameter and which of those shall be retained.
- (14) Location, type, materials, size and height of fencing, retaining walls and other screening including an elevation drawing.
- (15) Vertical cross-sectional view showing:
 - (a) Height of proposed structures.
 - (b) Number of stories.
 - (c) Location and access to underground parking.
 - (d) Proposed grades of each floor, including basements.
- (16) Plan of each proposed parking garage level.
- (17) Additional information deemed essential by the agent to permit adequate review of the plan.
- (18) The following data in tabular form:
 - (a) Area of parcel in square feet.
 - (b) Proposed gross floor area and the area of the above grade horizontal surface of any parking structure.
 - (c) Proposed floor area ratio and maximum permitted.
 - (d) Number and type of dwelling units.
 - (e) Number of parking and loading spaces required and proposed.
 - (f) Special exceptions or variances granted or requested.
 - (g) Landscaped open space required and proposed.
 - (h) Tabulation of tree canopy on the site at ten year maturity.
- (19) Provisions for erosion and sediment control and the disposition of natural and stormwater including the proposed location, sizes, types and grades of ditches, catch basins and pipes and connections to existing drainage systems. (Code 1978, 26-23).

Section 110-104. Exceptions.

The agent, after consultation with the zoning administrator, may waive the submission of some of the information required by section 110-103 if he determines that the proposed use or development may be adequately reviewed without some of the required information, if the proposed building or addition does not exceed two thousand (2,000) square feet of gross floor area and a site plan has previously been approved for the property. (Code 1978, 26-23).

Section 110-105. Review Standards.

In furtherance of the purposes of this chapter and to assure the public safety and general welfare, no site plan shall be approved unless the following are incorporated into the plan:

- (1) Provisions for safe and functionally efficient traffic circulation and control on the site, and access to adjacent sites and public rights-of-way;
- (2) Provisions for adequate fire protection approved by the fire marshal, and adequate water and sanitary sewer facilities approved by the director of utilities;
- (3) Compliance with design criteria, construction standards and specifications for required public improvements adopted by the Code of the City of Fairfax or by the Commonwealth of Virginia;
- (4) Provisions for pedestrian traffic and connection of proposed sidewalks and bicycle trails to the city's system where such system is existing or planned adjacent to the proposed development;
- (5) Provisions for adequate storm water management and erosion and sediment control measures as specified in this chapter;
- (6) Proof of easements required to develop or use the property as indicated n the plan;
- (7) Provisions for service roads on property bordering arterial streets where adopted city plans specifically indicated such roads. However, notwithstanding the requirements of sections 110-763,110-783 and 110-803, no proposed structure shall be located closer than ten (10) feet from the service road right-of-way or easement line;
- (8) Dedication to the city of rights-of-way for streets, service roads (if required) and other facilities for public use (e.g., utilities and park areas), and easements necessary for their construction and maintenance;
- (9) Delineation of each "no parking," reserved parking and handicapped parking area on the site:

- (10) Adequate provisions for refuse disposal. If dumpsters are used for refuse disposal, then each dumpster shall be located on a concrete pad with minimum dimensions of twenty (20) feet by twelve (12) feet and screened in accordance with the requirements contained in Division 10. Refuse disposal areas shall be located so that they are accessible by a disposal truck without impeding traffic or encroaching upon required parking spaces;
- (11)The underground installation of all on-site utilities in accordance with city and Applicable utility company standards. In addition, when the proposed development will result in moving or relocating existing overhead utilities located in adjoining rightsof-way, the applicant shall be responsible for placing such utilities under ground and dedicating any additional right-of-way or easement that is necessary. Equipment such as electric distribution transformers, switchgear, meter pedestals and telephone pedestals which is normal installed above ground in accordance with general accepted utility practice for underground distribution may be so installed. Temporary overhead facilities required for construction purposes shall be permitted. The city council may grant special exceptions to modify the requirements of this provision if the applicant clearly demonstrates that the requirements pertaining to the underground placement of utilities in adjacent rights-of-way will result in an expense which exceeds five (5) percent of the total cost of the proposed construction. Special exceptions shall only be granted by city council pursuant to the procedures and limitations established for special use permits set forth in section 110-366;
- (12) Provisions for adequate site and street lighting to provide safety and security for both pedestrian and vehicular traffic. Lighting fixture style shall be compatible with the architecture of the buildings located on the site. On-site lighting shall be directed downward and inward to prevent spill light on adjacent property. No lighting fixture within or immediately adjacent to any residential district shall exceed twelve (12) feet in height, nor shall any lighting fixture located elsewhere exceed twenty (20) feet in height. The site plan shall address lighting for facilities which may require special lighting. White light sources/luminaires shall be used to provide improved color rendition, unless otherwise approved by the agent. Levels of illumination shall be consistent with the foot candles and uniformity values specified in the illuminating Engineering Society Lighting Handbook.
- (13) Compliance with all requirements of this chapter.

Section 110-106. Screening

Screening from adjacent property shall be provided in accordance with the requirements contained in Division 10, Tree Preservation, Landscaping and Screening. (Code 1978, 26-25)

Section 110-107. Completion agreement and bond

- (a) Prior to approval of any site plan, there shall be executed by the owner or developer and submitted with the site plan an agreement in form and substance as approved by the city to construct all physical improvements required by the provisions of this chapter. A bond, with surety or condition acceptable to the city, in the amount of
 - (1) One hundred (100) percent of the estimated cost of all required improvements which are to be dedicated to public use or connected to a public facility; and
 - (2) Twenty-five (25) percent of the estimated cost of all other required physical improvements; and
 - (3) One hundred (100) percent of the estimated cost of all plant material required by this chapter or designated to be preserved in the development process.
- (b) All estimates of cost shall accompany the site agreement and shall be subject to approval by the site plan approving agent. The aforesaid agreement and bond shall be provided to ensure completion of all work or improvements therein stated within the time cited in the agreement and determined by the agent. The completion time may be extended by the city manager upon written application by the owner or developer, signed by all parties to the original agreement and to the bond. The adequacy, conditions and acceptability of any bond hereunder shall be determined by a bond committee appointed by the city manager. In any case where the bond committee has rejected any such agreement or bond, the owner or developer may appeal such decision to the city council.

(Code 1978, 26-26)

Section 110-108. Inspection and supervision during installation.

- (a) The construction standards for all off-site and on-site improvements required by this division shall conform to applicable plumbing, building, electrical, fire and health codes, and other applicable laws, ordinances and regulations. The director of public works shall approve the plans and specifications for all required improvements, and shall supervise inspection of the construction of such improvements to assure conformity.
- (b) The developer or owner shall notify the director of public works not less than twenty-four (24) hours prior to undertaking construction of streets, storm sewer work and other facilities to be publicly maintained.
- (c) The developer or owner shall provide adequate supervision of all work related to the development of the site, and shall have a responsible superintendent or foreman, together with one set of approved plans, profiles and specifications, available at the site at all times while work is being performed. (Code 1978, 26-27

Section 110-109. Certificates of Occupancy.

- (a) A certificate of occupancy shall be issued by the zoning administrator only for developments which conform to approved site plans.
- (b) Temporary certificate of occupancy:
 - (l) A temporary certificate of occupancy shall be issued for an approved project if remaining improvements are limited to landscaping and paving which cannot be completed because of adverse climatic conditions provided that each area to be paved has been provided with a dustless surface such as B-3 base coat and the zoning administrator has determined that the issuance of such certificate will not be detrimental to the public health, safety and welfare.
 - (2) A temporary certificate of occupancy shall also be issued for a completed section or phase of an approved project provided that it conforms to applicable regulations, it is independently functional with respect to the remainder of the project, a phasing plan has been approved, and all on-site and off-site improvements pertaining to the completed section have been completed, inspected and approved except as provided for in subsection (b)(1) of this section.
 - (3) A temporary certificate of occupancy shall be valid for a period of ninety (90) days from issuance and may be renewed for a single ninety-day period upon written application, by the owner or developer provided that all other work in progress conforms to the approved site plan and applicable requirements.
- (c) A permanent certificate of occupancy shall be issued only after:
 - (l) The owner or developer has submitted the appropriate application; and,
 - (2) All necessary inspections for on-site and off-site construction have been completed to the satisfaction of the zoning administrator; and
 - (3) A certified "as built" site plan has been filed for the project. The "as built" site plan may be a copy of the original approved site plan with an affidavit attached stating that all construction has been completed in compliance with the approved plan, or shall show all deviations from the approved plan with an affidavit attached stating that no deviations exist except those shown. The "as built" plan shall be certified by an engineer, architect or land surveyor to the limits of his license.
 - (4) The owner or developer, after completion of all off-site improvements and discharge of the performance bond, has provided a two-year warranty bond with surety equal to ten (l0) percent of the original completion bond in a form satisfactory to the city. (Code 1978 26-28).

Department of Community Development and Planning City of Fairfax, Virginia Section 110-110. Validity of approved site plans.

An approved site plan shall become null and void if no grading or construction has commenced on the site within twelve (12) months after approval. The agent may grant a single one-year extension upon written request of the applicant provided that the request is made at least thirty (30) days prior to the expiration date of the approved site plan. (Code 1978, 26-28).

Secs. 110-111—110-125. Reserved.




City of Fairfax

Department of Fire and Rescue Service

Office of Code Administration

10455 Armstrong Street Fairfax VA, 22030



SECTION F-3.6 Fire Lanes and Emergency Access and Roadways and Special Provisions

F-3.6 Designation.

The fire official shall designate fire lanes on public streets and on private property where necessary to ensure that firefighting and rescue apparatus has the required access to fire department connections, buildings and structures. Fire lanes shall have a minimum width of eighteen (18) feet or wider. Fire lanes serving structures greater than 30 feet in height or schools shall have a minimum clear width of 22 feet. Approved road widths see table 3.5.2. "Dead end" fire lanes over 150 feet in length shall be provided with an approved turnaround. Approved turnarounds, see table 3.5.1. All curved sections of fire lanes shall have a minimum outside radius of 45 feet.

Fire lanes shall not exceed 10% slope in any direction. Pavement sections shall be designed to support vehicles weighing up to 75,000 pounds. Where gates are to be installed across a fire lane, the following conditions must be observed:

- The gates must be maintained in an operable condition or be fixed in the open position.
- A means of manually opening the gate in the event of power failure must be provided.
- A key operated switch to the satisfaction of the fire official must be provided.

Department of Community Development and Planning City of Fairfax, Virginia

Table 3.6.1 Approved turnaround

Length (feet)	Width (feet)	Turnarounds Required
0-150	20	None Required
150-500	20	120' hammerhead or 60' Y 96' diameter cul-de-sac
501-750	26	120' Hammerhead or 60' Y 96" diameter cul-de-sac
Over 750	Special approval required	

Table 3.6.2 Standard Fire and Emergency Access Roadway.

Standard Requirements for parking restrictions

Street Width Curb to Curb	One Way Traffic	Two Way Traffic
Less than 20'	No parallel parking on either side of the street	No parallel parking on either side of street
20' to 26'	Parallel parking on one side As decided by and approved by Fire Marshal	No Parallel parking on either side of street
26' to 32'	Parallel parking allowed both sides of street	Parallel parking on one side As approved and decided by Fire Marshal
32' or greater	Parallel parking allowed on both sides of street	Parallel parking allowed on both sides of street

F-3.6.3. Signs and markings.

The property owner or designee shall supply and install signs and other required markings to delineate fire lanes as directed by the fire official. The cost of which will be born by the property owner or designee.

F-3.6.4. Specifications.

Fire lanes shall conform to the following specifications:

Metal construction, dimensions twelve (12) inches by eighteen (18) inches. Red letters on a reflective white background with three- eighth's -inch red trim strip around the entire outer edge of the sign. Signs shall be mounted with the top of the signs seven (7) feet above grade.

Lettering size to be as follows:

"NO PARKING" - 2 inches,

Arrow's 1 inch solid, Spacing between words to be uniform.

[&]quot;OR" - 1 inch,

[&]quot;STANDING" - 2 inches,

[&]quot;FIRE LANE" - 2 ½ inches,

Type "A" arrow to the right



Type "B" arrow to the left



Type "C" arrows in both directions



Type "D' two signs back to back perpendicular to the street.

- 1. Other type signs or markings approved by the fire official.
- 2. Curbing shall be painted yellow within the limits of the fire lane.
- 3. Striping may be required to be marked as needed on the road surface.

Section F-3.6.5 Fire Lane restrictions

- (1) It shall be unlawful for any person to park in the designated and marked area, except for school buses that are in the process of receiving or discharging students as long as the bus driver remains with the bus at all times. For the purposes of this subsection, the term "park" shall mean the standing of a vehicle, whether occupied or not, except while obeying traffic regulations, signs or signals or except while involuntarily stopping because of causes beyond the control of the operator of the vehicle.
- (2) In any prosecution under this section, proof that the vehicle described in the complaint, summons or warrant was parked in violation of this code, together with proof that the defendant was at the time of such parking the registered owner of the vehicle, shall constitute a prima facie evidentiary presumption that such registered owner of the vehicle was the person who parked the vehicle at the place and at the time such violation occurred.
- (3) In addition, the vehicle parked in violation of this section may be impounded by the City of Fairfax Fire Marshal's Office, Fairfax Police Department or the city fire marshal's office and held until the penalty provided and the towing and storage charges incurred are paid.
- (4) This section shall be enforced by the city fire marshal or his staff and the city police department.
- (5) Penalty for violation of this section shall be a fine of fifty dollars (\$100.00) for each offense.

Section F-3.6.6 Existing signs.

It shall be unlawful for any person to deface, injure, tamper with, remove, destroy or impair the usefulness of any posted fire lane sign installed under the provisions of this code.

City of Fairfax Digital Data Submission Requirements for GIS

Background:

The City of Fairfax has developed a geographic information system (GIS) to store, manage, and maintain geographic data. The local land development, engineering, and surveying communities have also embraced digital technologies in their own fields. Because development plans are now created using computer aided design and drafting (CAD) software, it is the goal of the City of Fairfax to utilize these techniques to enhance and expedite the design and plan review process within the City and help maintain a digital database of geographic information. For this, requirements have been implemented to allow CAD and other GIS data to be integrated into the City's GIS while preserving the referential and positional accuracy of the original measurements.

Requirements:

- 1. Data *must* be in DXF format if from AutoCAD, Microstation or another Cad software program, or ESRI Shapefile if from a GIS software program. (DWG and DGN files will *not* be accepted)
- 2. Data *must* be projected in Virginia State Plane North, NAD 83 Harn. Data *must* fit in seamlessly with City's GIS data layers.
- **3.** Data *must* be separated into *individual* thematic layers and labeled accordingly.

<u>Layers Required</u> (project dependant)

Building footprints

Parking configuration (including islands, no parking stripes) (Commercial)

Driveways (Residential)

Street Centerlines

Parcel / Property boundaries

Utility Lines (sewer, water, electric, gas, fiber optic cable, phone lines, etc.)

Sidewalks

Easements

Landscaping/tree cover (post development)

Topography (to include vertical datum reference in National Geodetic Vertical Datum of 1929 (NGVD29)).

Minimum of four (4) digital grid tics in NAD 83 Virginia State Plane Coordinate System.

Right-of-way

Stormwater lines, structures, outlets

Best Management Practice (BMP) (include polygon showing drainage area to each BMP)

4. A text file or word document *must* accompany the digital data with a description of each layer. POCs for electronic plat submission requirements are with Maurice Rioux, GIS Manager with the Dept. of Information Technology at maurice.rioux@fairfaxva.gov

This information is also available on the City's website www.fairfaxva.gov/it/gis.asp



"As-Built" Review Requirement Checklist

Project Name:_		Project No
Project Address	:	Tax Map No
Phone:		
Fairfax City Co conforms to the		nt to Chapters 86-4(h) and 110-109(c)(3) of thedo hereby certify that this as-built s, and represents the actual conditions on this site as
(signature)	
		(Seal)
architect or land		et of each plan and sign by a certified engineer,
A. B. C. D. E. F. G. H.	Boundary of site Location of buildings, setbacks Address of building Site Plan number Parking spaces and loading are Fire lanes (as applicable) Actual Site Grading and Critic Drainage Divides	as
2. LANDS	CAPING	
A.	Location and type of all plant in Revised planting schedule to re	naterial effect all changes in plant material

3.	STORM SEWER		
	ABCDEFGH.	Invert elevations "in" and "out" – existing structure at connection Size of pipe Distance between structures centerline to centerline Type of structure For yard inlets, the number and locations of throats Elevation and structure top All road culverts carrying discharge from storm systems and/or crossing streets For field connection, give pipe size, invert elevation at upper end and top, and appropriate length	
4.	SANITARY SEWER (SEE ITEM 6)		
	ABCDEFG.	Invert elevations, "in" and "out" – existing structure at connection Distance between centerline of structure Elevation of top Horizontal location of structure Lateral table or equivalent information on plan and profile. (Note: Plan and profile must be on same sheet.) Overall sanitary layout sheet Cleanout Locations	
4-A.	WATER LINE		
	ABCDE.	Invert elevations, "In" and "out" – existing structure at connection Distance between centerline of structure Elevation of top Horizontal location of structure Lateral table or equivalent information on plan and profile. (Note: Plan and profile must be on same sheet.)	
5.	BMP/SWM Facilities		
	A.	Locate storm structure as shown - all tops, throats, inverts, elevations - pipe size, opening for overflow, top of wall and orifice elevation	
	B.	Adequate spot elevations around entire pond depicting the shape (Note: Minimum ten (10) along top and crest of dam width.)	
	C.	Spot elevation through drainage way to outfall and spillway (Note: give width of spillway.)	
	D.	Provide all information for underground detention and BMP Facilities (Note: that underground detention is in place.)	
	E.	Show access easement (with Deed Book and Page Number) for maintenance of pond.	
	F.	BMP and SWM Facility Inspection at 2 Year Warranty Bond Release	

6.	EASEMENTS		
	A.	Provide Deed Book and Page Number for sanitary, storm and access easements	
7.	SUBMISSION		
	A.	Submit five sets of drawings and electronic submission of approved site plan with all revisions and As-Built drawing in pdf format.	
8.	PAYMENT		
	A.	Submit review fee of \$550 plus \$110 for each acre of fraction thereof.	